

Aluma-Grip™ AFT-701

Aluma-Grip AFT-701 is a 30-mil thick, heavy-duty, pressure-sensitive, 40-year-cycle, duct joint rolled sealant with a tensile strength of 445-psi average. AFT-701 provides an aggressive water-resistant grip to most surfaces including sheet metal, duct board, flex duct, PVC-coated duct, and duct wrap vapor barriers. Made with THE GRAY MATTER™ Elastomeric Modified Butyl Rubber, AFT-701 is even suitable for sub-grade application on PVC-coated duct.



All-Purpose 1602

All-Purpose 1602 is a pressure sensitive duct joint, metal seam (must be coated first), and general purpose rolled mastic sealant. The fabric backing allows paint to be applied easier for a customized look. It provides an instant, aggressive grip to most surfaces including sheet metal, duct board, and flex-duct for indoor applications.



BRT-801

BRT-801 is a 30 mil. composite black high density, water resistant, polyethylene hip & ridge sealant for use under tile and roof applications. Made with THE GRAY MATTER™, Elastomeric Modified Butyl Rubber, it has an aggressive grip, superior long-term adhesion, and stays flexible during application. It is asphalt and solvent free and seals immediately upon contact.



RMR-6325

RMR-6325 is a white, surface and shape adapting rubber membrane used for flashing and sealing unusual roofing needs, including fasteners on metal roof installations. It has an aggressive grip, superior long-term adhesion, and stays flexible during application, assuring an immediate seal on contact. RMR-6325's pressure sensitive properties allow for a fast, clean, and easy application.



TGM-3300

TGM-3300 is a butyl-based material between two release liners capable of bonding a variety of items together. It offers an aggressive grip, superior long-term bonding, and stays flexible during application, assuring immediate adhesion on contact.



TPO-2265

TPO-2265 is a white thermoplastic polyolefin backed self-adhering membrane with proven exterior performance that has an ideal thickness, aggressive grip and adhesion, provides leak-proof results, and is perfect for seams. Its improved butyl adhesive/sealant stays flexible and provides an easy, fast application.

