

Kwik-Stik is a superior quality, self-stick gasket tape material. The Neoprene and Urethane products offered have been on the market for many years and have passed the test of time. The adhesives used have been chosen for their dependability, holding power and wide temperature range.

NEOPRENE GASKET

OVERVIEW

Closed cell, medium density neoprene sponge meets all standards for use on Access Doors in high velocity installations. It can be used on multi-blade dampers blade edges and similar applications where airtightness and insulation qualities are needed. Self-Adhesive, peel-off backing offers high tack adhesion to metal surfaces. Adhesion improves with time. Metal should be clean and free of grease and oils.



TECHNICAL DATA

Operating Temperature Range	-30° to 200° F (-35° to 94° C)
-----------------------------	-----------------------------------

PART NUMBERS	PRODUCT DESCRIPTION (THICKNESS X WIDTH X LENGTH)
304605	1 Case w/ (24) 1/8" x 1/2" x 50' Rolls
304607	1 Case w/ (16) 1/4" x 3/4" x 25' Rolls
304608	1 Case w/ (16) 3/8" x 3/4" x 20' Rolls

URETHANE GASKET

OVERVIEW

Polyurethane foam (polyester) is backed with a dependable high tack adhesive with peel-off paper backing. This economical foam tape is a prominent tool known for its lightness, resilience and resistance to oils, moisture and many chemicals encountered in HVAC applications.



TECHNICAL DATA

Operating Temperature Range	-30° to 200° F (-35° to 94° C)
-----------------------------	-----------------------------------

PART NUMBER	PRODUCT DESCRIPTION (THICKNESS X WIDTH X LENGTH)
304609	1 Case w/ (24) 3/16" x 1/2" x 50' Rolls
304610	1 Case w/ (16) 1/4" x 3/4" x 40' Rolls
304611	1 Case w/ (16) 3/8" x 3/4" x 25' Rolls