



Non-Flam TRAVEL-TACK is a self-contained, instant-tacking portable spray system with a non-flammable propellant engineered to deliver a web spray pattern. Non-Flam TRAVEL-TACK's portability, limited equipment clean-up, and low equipment cost make this adhesive ideal for shop or field use.

PART NUMBERS

323821	1 #40 Cylinder (blue green)
--------	-----------------------------

TECHNICAL DATA

Color	Blue Green
Consistency	Aerosol spray
Spray Pattern	Variable web
Odor	Light
Base	Polymer
Vapor Pressure	350 mm
Solvent	Methylene Chloride
Approx. Coverage	125 sq ft/lb of adhesive
Initial Bonding Time	30 Seconds
Dry Time	4 minutes
Adhesion	Excellent
Service Temperature	-40°F to 200°F (-40°C to 93°C)
Flammability	Nonflammable
Surface Burning	Flame Spread 5 Smoke Developed 20 When tested in accordance with ASTM E84
Water Resistance	Excellent
Mildew Resistance	Good
VOC	<65 g/l
Packaging	#40, Aerosol cylinder
Net Weight	30 lb

APPLICATION

Temperature	60°F to 90°F (15.5°C to 32.2°C) (Keep at 70°F for optimum performance. If cylinder temperature falls below 70°F, move it to a warm area until optimum performance is achieved.)
Method	Apply according to SMACNA specifications and local codes.
Preparation	Surface must be dry and free of dirt, oil, moisture and grease.
Rate	16 oz per minute
Clean Up	UN-TACK™ Cleaner/Adhesive Remover, petroleum solvents or mineral spirits

STORAGE

Temperature	60°F to 95°F (15°C to 35°C)
Shelf Life	One year (unopened)

PRECAUTIONS

Do not expose to heat or store above 100°F. Do not puncture or incinerate. Small canisters are not re-fillable. When empty, dispose by following local code requirements. Review Material Safety Data Sheet for safety information prior to use.

For Industrial Professional Use Only.